CAT | FLOORING ACCESSORIES

Updated: May 2026

Product Technical Data Sheet



Catalogue Reference	AID50
Uniclass2015	Pr_35_90_31_84 STAIR TRIMS
General Description	Stair Tread Insert Disc
Material	Aluminium Alloy 6063 T6
Gauge	3.0 mm
Pack Quantity	25
Diameter	50 mm
Finishes Available & Light Reflective Values	Mill Aluminium - LRV: 71.65
Slip Resistance Values	SRV Wet: 45 SRV Dry: 73
Fixing	Adhesive. We recommend STYCCO FLEX rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.
Application	For rebating into stone and wooden steps to provide a visual aid and slip resistance. Small variations in dimensions may occur and therefore rebating should be to suit the delivered product. Installation guide available.
Suitability	Medium to heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500 sales@catflooringaccessories.com www.catflooringaccessories.com