



Product Technical Data Sheet



Catalogue Reference	AN15/55
Uniclass2015	Pr_35_90_31_74 RIGID STAIR NOSINGS
General Description	Single Channel/Square Front Stair Nosing. Supplied with choice of infill.
Nosing Construction	Stair Nosing With Infill
Material	Aluminium Alloy 6063 T6
Tread Dimension	66 mm
Nose Dimension	55 mm
Gauge	4.0 mm ramping down to 1mm
Supplied Cut To Size, up to a maximum length of	3200 mm
Finishes Available & Light Reflective Values	<p>Mill Aluminium - LRV: 71.65</p> <p>Infills</p> <p>Castellated PVC</p> <p>Black - LRV: 4.25</p> <p>Nimbus - LRV: 4.77</p> <p>Regency - LRV: 5.16</p> <p>Rustic - LRV: 5.52</p> <p>Claret - LRV: 5.83</p> <p>Peat - LRV: 5.88</p> <p>Spruce - LRV: 6.38</p> <p>Mid Blue - LRV: 6.53</p> <p>Granite - LRV: 7.02</p> <p>Jade - LRV: 7.33</p> <p>Poppy - LRV: 10.01</p> <p>Olive - LRV: 10.27</p> <p>Fawn - LRV: 11.27</p> <p>Flint - LRV: 11.27</p> <p>Light Grey - LRV: 12.33</p> <p>Gold - LRV: 16.84</p> <p>Ivory - LRV: 37.42</p> <p>Polar Grey - LRV: 42.53</p> <p>Porth Stone - LRV: 52.91</p> <p>Yellow - LRV: 54.91</p> <p>White - LRV: 84.22</p>

	<p>Infills</p> <p>Smooth Textured PVC</p> <p>Black - LRV: 4.47 Light Grey - LRV: 12.74 Polar Grey - LRV: 42.73 Porth Stone - LRV: 53.11</p> <p>Infills</p> <p>ATI49.5 Aluminium</p> <p>Black Anodised - LRV: 4.80 Bronze - LRV: 10.10 Light Bronze - LRV: 27.25 Satin Aluminium - LRV: 65.40 Mill Aluminium - LRV: 71.65 Polished Aluminium - LRV: 75.55</p> <p>Infills</p> <p>Olympic Grip</p> <p>Black - LRV: 4.85</p>
Screw Size	6
Additional Information	This product is also available in Mill Aluminium with a heavy-duty anti-slip glass-fibre reinforced plastic infill for external/wet installations. Product Reference: AN15/55 GRP
Application	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. Also suitable for direct fixing to concrete stairs.
Suitability	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.


Infill Options



Infill	Castellated PVC Insert
Material	PVC Compound
Slip Resistance Values	SRV Wet: 76 SRV Dry: 85
Drilling	Drilled for concealing plugs Undrilled Drilled with retro fit infill



Infill	Smooth Textured PVC Insert
Material	PVC Compound
Slip Resistance Values	SRV Wet: 56 SRV Dry: 65
Drilling	Drilled for concealing plugs Undrilled Drilled with retro fit infill



Infill	ATI49.5 Aluminium Insert
Material	Aluminium Alloy 6063 T6
Slip Resistance Values	SRV Wet: 54 SRV Dry: 82

Drilling	Undrilled Drilled with retro fit infill
-----------------	--



Infill	Olympic Grip Insert
Material	Aluminium Oxide
Slip Resistance Values	SRV Wet: 71 SRV Dry: 102
Drilling	Undrilled Drilled with retro fit infill

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com