



Product Technical Data Sheet



| | |
|---|---|
| Catalogue Reference | AN15/55R BA |
| Uniclass2015 | Pr_35_90_31_74 RIGID STAIR NOSINGS |
| General Description | Single Channel/Raked Front Stair Nosing. Supplied with choice of infill. |
| Nosing Construction | Stair Nosing With Infill |
| Material | Aluminium Alloy 6063 T6 |
| Tread Dimension | 66 mm |
| Nose Dimension | 55 mm |
| Gauge | 4.0 mm ramping down to 1mm |
| Supplied Cut To Size, up to a maximum length of | 2500 mm |
| Finishes Available & Light Reflective Values | <p>Black Anodised - LRV: 4.80</p> <p>Infills</p> <p>Castellated PVC</p> <p>Black - LRV: 4.25 Nimbus - LRV: 4.77 Regency - LRV: 5.16 Rustic - LRV: 5.52 Claret - LRV: 5.83 Peat - LRV: 5.88 Spruce - LRV: 6.38 Mid Blue - LRV: 6.53 Granite - LRV: 7.02 Jade - LRV: 7.33 Poppy - LRV: 10.01 Olive - LRV: 10.27 Fawn - LRV: 11.27 Flint - LRV: 11.27 Light Grey - LRV: 12.33 Gold - LRV: 16.84 Ivory - LRV: 37.42 Polar Grey - LRV: 42.53 Porth Stone - LRV: 52.91 Yellow - LRV: 54.91 White - LRV: 84.22</p> |

| | |
|------------------------------------|--|
| | <p>Infills</p> <p>Smooth Textured PVC</p> <p>Black - LRV: 4.47 Light Grey - LRV: 12.74 Polar Grey - LRV: 42.73 Porth Stone - LRV: 53.11</p> <p>Infills</p> <p>ATI49.5 Aluminium</p> <p>Black Anodised - LRV: 4.80 Bronze - LRV: 10.10 Light Bronze - LRV: 27.25 Satin Aluminium - LRV: 65.40 Mill Aluminium - LRV: 71.65 Polished Aluminium - LRV: 75.55</p> <p>Infills</p> <p>Olympic Grip</p> <p>Black - LRV: 4.85</p> |
| Screw Size | 6 |
| Additional Information | This product is also available in Mill Aluminium with a heavy-duty anti-slip glass-fibre reinforced plastic infill for external/wet installations. Product Reference: AN15/55R GRP |
| Application | To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. |
| Suitability | For stairs with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath. |
| Post Consumer Recyclability | This product is 100% recyclable at suitable disposal centres. |

Infill Options



| | |
|-------------------------------|--|
| Infill | Castellated PVC Insert |
| Material | PVC Compound |
| Slip Resistance Values | SRV Wet: 76 SRV Dry: 85 |
| Drilling | Drilled for concealing plugs Undrilled Drilled with retro fit infill |



| | |
|-------------------------------|--|
| Infill | Smooth Textured PVC Insert |
| Material | PVC Compound |
| Slip Resistance Values | SRV Wet: 56 SRV Dry: 65 |
| Drilling | Drilled for concealing plugs Undrilled Drilled with retro fit infill |



| | |
|-------------------------------|----------------------------|
| Infill | ATI49.5 Aluminium Insert |
| Material | Aluminium Alloy 6063 T6 |
| Slip Resistance Values | SRV Wet: 54 SRV Dry: 82 |

| | |
|-----------------|--|
| Drilling | Undrilled Drilled with retro fit infill |
|-----------------|--|



| | |
|-------------------------------|--|
| Infill | Olympic Grip Insert |
| Material | Aluminium Oxide |
| Slip Resistance Values | SRV Wet: 71 SRV Dry: 102 |
| Drilling | Undrilled Drilled with retro fit infill |

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com