



Product Technical Data Sheet



Catalogue Reference	AN15/55R
Uniclass2015	Pr_35_90_31_74 RIGID STAIR NOSINGS
General Description	Single Channel/Raked Front Stair Nosing. Supplied with choice of infill.
Collection	Designer Collection™
Nosing Construction	Stair Nosing With Infill
Material	Aluminium Alloy 6063 T6
Tread Dimension	66 mm
Nose Dimension	55 mm
Gauge	4.0 mm ramping down to 1mm
Supplied Cut To Size, up to a maximum length of	2500 mm
Finishes Available & Light Reflective Values	<p>Light Bronze - LRV: 27.25</p> <p><b>Infills</b></p> <p><b>Castellated PVC</b></p> <p>Black - LRV: 4.25          Nimbus - LRV: 4.77          Regency - LRV: 5.16          Rustic - LRV: 5.52          Claret - LRV: 5.83          Peat - LRV: 5.88          Spruce - LRV: 6.38          Mid Blue - LRV: 6.53          Granite - LRV: 7.02          Jade - LRV: 7.33          Poppy - LRV: 10.01          Olive - LRV: 10.27          Fawn - LRV: 11.27          Flint - LRV: 11.27          Light Grey - LRV: 12.33          Gold - LRV: 16.84          Ivory - LRV: 37.42          Polar Grey - LRV: 42.53          Porth Stone - LRV: 52.91</p>

	<p>Yellow - LRV: 54.91 White - LRV: 84.22</p> <p><b>Infills</b></p> <p><b>Smooth Textured PVC</b></p> <p>Black - LRV: 4.47 Light Grey - LRV: 12.74 Polar Grey - LRV: 42.73 Porth Stone - LRV: 53.11</p> <p><b>Infills</b></p> <p><b>ATI49.5 Aluminium</b></p> <p>Black Anodised - LRV: 4.80 Bronze - LRV: 10.10 Light Bronze - LRV: 27.25 Satin Aluminium - LRV: 65.40 Mill Aluminium - LRV: 71.65 Polished Aluminium - LRV: 75.55</p> <p><b>Infills</b></p> <p><b>Olympic Grip</b></p> <p>Black - LRV: 4.85</p>
<b>Screw Size</b>	6
<b>Additional Information</b>	This product is also available in Mill Aluminium with a heavy-duty anti-slip glass-fibre reinforced plastic infill for external/wet installations. Product Reference: AN15/55R GRP
<b>Application</b>	To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino.
<b>Suitability</b>	Light to medium foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, offices and apartment buildings.
<b>Post Consumer Recyclability</b>	This product is 100% recyclable at suitable disposal centres.

# Infill Options



<b>Infill</b>	Castellated PVC Insert
<b>Material</b>	PVC Compound
<b>Slip Resistance Values</b>	SRV Wet: 76 SRV Dry: 85
<b>Drilling</b>	Drilled for concealing plugs Undrilled Drilled with retro fit infill



<b>Infill</b>	Smooth Textured PVC Insert
<b>Material</b>	PVC Compound
<b>Slip Resistance Values</b>	SRV Wet: 56 SRV Dry: 65
<b>Drilling</b>	Drilled for concealing plugs Undrilled Drilled with retro fit infill



<b>Infill</b>	ATI49.5 Aluminium Insert
<b>Material</b>	Aluminium Alloy 6063 T6
<b>Slip Resistance Values</b>	SRV Wet: 54 SRV Dry: 82

Drilling	Undrilled Drilled with retro fit infill
----------	--



Infill	Olympic Grip Insert
Material	Aluminium Oxide
Slip Resistance Values	SRV Wet: 71 SRV Dry: 102
Drilling	Undrilled Drilled with retro fit infill

**Made with Precision, Finished with Care**

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

[sales@catflooringaccessories.com](mailto:sales@catflooringaccessories.com)

[www.catflooringaccessories.com](http://www.catflooringaccessories.com)