CAT | FLOORING ACCESSORIES

Updated: May 2026

# Product Technical Data Sheet




| | |
|---|---|
| Catalogue Reference | AN15R GRP |
| Uniclass2015 | Pr_35_90_31_74 RIGID STAIR NOSINGS |
| General Description | Single Channel/Raked Front Stair Nosing. Supplied with GRP infill. |
| Nosing Construction | Stair Nosing With Infill |
| Material | Aluminium Alloy 6063 T6 |
| Tread Dimension | 63.3 mm |
| Nose Dimension | 30 mm |
| Gauge | 4.0 mm ramping down to 1mm |
| Supplied Cut To Size, up to a maximum length of | 2400 mm |
| Finishes Available & Light Reflective Values | Mill Aluminium - LRV: 71.65<br>**Infills**<br>**GRPTI49.5 Infill**<br>Black - LRV: 4.76<br>Yellow - LRV: 47.07<br>Grey - LRV: 32.13 |
| Screw Size | 6 |
| Application | To finish the nose edge of stone and timber stairs and stairs fitted with ceramics or hard flooring, e.g. laminates, LVT, vinyl, lino. |
| Suitability | Exterior and wet environments and very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings. |

# Infill Options




| | |
|---|---|
| Infill | GRPTI49.5 Infill |
| Material | Glass-reinforced plastic with quartz grit bonded on top (with resin) |
| Slip Resistance Values | SRV Wet: 73<br>SRV Dry: 81 |
| Drilling | Drilled with retro fit infill<br>Undrilled with infill stuck in channel<br>Undrilled with infill supplied loose |

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500 sales@catflooringaccessories.com www.catflooringaccessories.com