


Product Technical Data Sheet



| | |
|--|--|
| Catalogue Reference | AN4 |
| Uniclass2015 | Pr_35_90_31_74 RIGID STAIR NOSINGS |
| General Description | Castellated Tread/Square Front Stair Nosing. |
| Nosing Construction | Solid Stair Nosing |
| Material | Aluminium Alloy 6063 T6 |
| Tread Dimension | 44 mm |
| Nose Dimension | 21.5 mm |
| Gauge | 3.5 mm |
| Lengths Available | Supplied cut to customer sizes up to: 3200 mm |
| Finishes Available & Light Reflective Values | Mill Aluminium - LRV: 71.65 |
| Slip Resistance Values | SRV Wet: 54 SRV Dry: 82 |
| Drilling | Drilled for countersunk screws Undrilled |
| Screw Size | 6 |
| Application | For finishing the nose edge of stairs fitted with LVT, vinyl, lino. Can be rebated into wooden steps. Installation guide available. |
| Suitability | Medium to heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings. |
| Post Consumer Recyclability | This product is 100% recyclable at suitable disposal centres. |

Made with Precision, Finished with Care

Carpet Accessory Trims Limited. Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com