


Product Technical Data Sheet



Catalogue Reference	AN4
Uniclass2015	Pr_35_90_31_74 RIGID STAIR NOSINGS
General Description	Castellated Tread/Square Front Stair Nosing.
Nosing Construction	Solid Stair Nosing
Material	Aluminium Alloy 6063 T6
Tread Dimension	44 mm
Nose Dimension	21.5 mm
Gauge	3.5 mm
Lengths Available	Supplied cut to customer sizes up to: 3200 mm
Finishes Available & Light Reflective Values	Polished Aluminium - LRV: 75.55
Slip Resistance Values	SRV Wet: 54 SRV Dry: 82
Drilling	Drilled for countersunk screws Undrilled
Screw Size	6
Application	For finishing the nose edge of stairs fitted with LVT, vinyl, lino. Can be rebated into wooden steps. Installation guide available.
Suitability	Medium to heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Made with Precision, Finished with Care

Carpet Accessory Trims Limited. Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com