CAT | FLOORING ACCESSORIES

Updated: May 2026

# Product Technical Data Sheet




| | |
|---|---|
| Catalogue Reference | AN51/55 |
| Uniclass2015 | Pr_35_90_31_74 RIGID STAIR NOSINGS |
| General Description | Single Channel/Square Front Stair Nosing. Supplied with choice of infill. |
| Collection | Designer Collection™ |
| Nosing Construction | Stair Nosing With Infill |
| Material | Aluminium Alloy 6063 T6 |
| Tread Dimension | 62 mm |
| Nose Dimension | 55 mm |
| Gauge | 5.0 mm |
| Supplied Cut To Size, up to a maximum length of | 2750 mm |
| Finishes Available & Light Reflective Values | Bronze - LRV: 10.10<br>**Infills**<br>**Castellated PVC**<br>Black - LRV: 4.25<br>Nimbus - LRV: 4.77<br>Regency - LRV: 5.16<br>Rustic - LRV: 5.52<br>Claret - LRV: 5.83<br>Peat - LRV: 5.88<br>Spruce - LRV: 6.38<br>Mid Blue - LRV: 6.53<br>Granite - LRV: 7.02<br>Jade - LRV: 7.33<br>Poppy - LRV: 10.01<br>Olive - LRV: 10.27<br>Fawn - LRV: 11.27<br>Flint - LRV: 11.27<br>Light Grey - LRV: 12.33<br>Gold - LRV: 16.84<br>Ivory - LRV: 37.42<br>Polar Grey - LRV: 42.53<br>Porth Stone - LRV: 52.91<br>Yellow - LRV: 54.91 |

| | |
|---|---|
| | Cloud - LRV: 55.18<br>White - LRV: 84.22<br>Infills<br>Smooth Textured PVC<br>Black - LRV: 4.47<br>Light Grey - LRV: 12.74<br>Polar Grey - LRV: 42.73<br>Porth Stone - LRV: 53.11<br>Infills<br>ATI49.5 Aluminium<br>Black Anodised - LRV: 4.80<br>Bronze - LRV: 10.10<br>Light Bronze - LRV: 27.25<br>Satin Aluminium - LRV: 65.40<br>Mill Aluminium - LRV: 71.65<br>Polished Aluminium - LRV: 75.55<br>Infills<br>Olympic Grip<br>Black - LRV: 4.85 |
| Screw Size | 8 |
| Compatible Products | ANEXT, ANRE25, ANE NAP |
| Additional Information | This product is also available in Mill Aluminium with a heavy-duty anti-slip glass-fibre reinforced plastic infill for external/wet installations. Product Reference: AN51/55 GRP |
| Application | For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and ANEXT extension tread. Installation guide available. |
| Suitability | Light to medium foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, offices and apartment buildings. |
| Post Consumer Recyclability | This product is 100% recyclable at suitable disposal centres. |

# Infill Options




| | |
|---|---|
| Infill | Castellated PVC Insert |
| Material | PVC Compound |
| Slip Resistance Values | SRV Wet: 76<br>SRV Dry: 85 |
| Drilling | Drilled for concealing plugs<br>Undrilled<br>Drilled with retro fit infill |

| | |
|---|---|
| Infill | Smooth Textured PVC Insert |
| Material | PVC Compound |
| Slip Resistance Values | SRV Wet: 56<br>SRV Dry: 65 |
| Drilling | Drilled for concealing plugs<br>Undrilled<br>Drilled with retro fit infill |




| | |
|---|---|
| Infill | ATI49.5 Aluminium Insert |
| Material | Aluminium Alloy 6063 T6 |
| Slip Resistance Values | SRV Wet: 54<br>SRV Dry: 82 |

| | |
|---|---|
| Drilling | Undrilled<br>Drilled with retro fit infill |

| | |
|---|---|
| Infill | Olympic Grip Insert |
| Material | Aluminium Oxide |
| Slip Resistance Values | SRV Wet: 71<br>SRV Dry: 102 |
| Drilling | Undrilled<br>Drilled with retro fit infill |

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500 sales@catflooringaccessories.com www.catflooringaccessories.com