


Product Technical Data Sheet



Catalogue Reference	AN51/55R
Uniclass2015	Pr_35_90_31_74 RIGID STAIR NOSINGS
General Description	Single Channel/Raked Front Stair Nosing. Supplied with choice of infill.
Nosing Construction	Stair Nosing With Infill
Material	Aluminium Alloy 6063 T6
Tread Dimension	62 mm
Nose Dimension	55 mm
Gauge	5 mm
Supplied cut to customer sizes up to:	2500 mm
Finishes Available & Light Reflective Values	<p>Polished Aluminium - LRV: 75.55</p> <p>Infills</p> <p>Castellated PVC</p> <p>Black - LRV: 4.25 White - LRV: 84.22 Light Grey - LRV: 12.33 Flint - LRV: 11.27 Granite - LRV: 7.02 Rustic - LRV: 5.52 Fawn - LRV: 11.27 Ivory - LRV: 37.42 Spruce - LRV: 6.38 Jade - LRV: 7.33 Regency - LRV: 5.16 Mid Blue - LRV: 6.53 Nimbus - LRV: 4.77 Peat - LRV: 5.88 Yellow - LRV: 54.91 Poppy - LRV: 10.01 Claret - LRV: 5.83 Porth Stone - LRV: 52.91 Polar Grey - LRV: 42.53</p> <p>Infills</p> <p>Smooth Textured PVC</p>

Black - LRV: 4.47
Light Grey - LRV: 12.74
Polar Grey - LRV: 42.73
Porth Stone - LRV: 53.11

Infills

ATI49.5 Aluminium

Mill Aluminium - LRV: 71.65
Satin Aluminium - LRV: 65.40
Polished Aluminium - LRV: 75.55
Bronze - LRV: 10.10
Light Bronze - LRV: 27.25
Black Anodised - LRV: 4.80


Infills

Olympic Grip

Black - LRV: 4.85

Drilling	Drilled for concealing plugs Undrilled Drilled with retro fit infill
Screw Size	8
Compatible Products	ANEXT, ANRE25, ANE
Application	For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and ANEXT extension tread. Installation guide available.
Suitability	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Infill Options



Infill	Castellated PVC Insert
Material	PVC Compound
Slip Resistance Values	SRV Wet: 76 SRV Dry: 85
Drilling	Drilled for concealing plugs Undrilled Drilled with retro fit infill



Infill	Smooth Textured PVC Insert
Material	PVC Compound
Slip Resistance Values	SRV Wet: 56 SRV Dry: 65
Drilling	Drilled for concealing plugs Undrilled Drilled with retro fit infill



Infill	ATI49.5 Aluminium Insert
Material	Aluminium Alloy 6063 T6
Slip Resistance Values	SRV Wet: 54 SRV Dry: 82
Drilling	Undrilled Drilled with retro fit infill

Infill	Olympic Grip Insert
Material	Aluminium Oxide
Slip Resistance Values	SRV Wet: 71 SRV Dry: 102
Drilling	Undrilled Drilled with retro fit infill

Made with Precision, Finished with Care

Carpet Accessory Trims Limited. Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com