



Product Technical Data Sheet



Catalogue Reference	AN59SL
Uniclass2015	Pr_35_90_31_74 RIGID STAIR NOSINGS
General Description	Single Channel/Square Front Stair Nosing. Supplied with choice of infill.
Collection	Designer Collection™
Nosing Construction	Stair Nosing With Infill
Material	Aluminium Alloy 6063 T6
Tread Dimension	59 mm
Nose Dimension	30 mm
Gauge	2.5 mm
Lengths Available	Supplied cut to customer sizes up to: 2750 mm
Finishes Available & Light Reflective Values	<p>Light Bronze - LRV: 27.25</p> <p>Infills</p> <p>ATI49.5 Aluminium</p> <p>Mill Aluminium - LRV: 71.65 Satin Aluminium - LRV: 65.40 Polished Aluminium - LRV: 75.55 Bronze - LRV: 10.10 Light Bronze - LRV: 27.25 Black Anodised - LRV: 4.80</p> <p>Infills</p> <p>Castellated PVC</p> <p>Black - LRV: 4.25 White - LRV: 84.22 Light Grey - LRV: 12.33 Flint - LRV: 11.27 Granite - LRV: 7.02 Rustic - LRV: 5.52 Fawn - LRV: 11.27 Ivory - LRV: 37.42 Spruce - LRV: 6.38 Jade - LRV: 7.33 Regency - LRV: 5.16 Mid Blue - LRV: 6.53</p>

	<p>Nimbus - LRV: 4.77 Peat - LRV: 5.88 Yellow - LRV: 54.91 Poppy - LRV: 10.01 Claret - LRV: 5.83 Porth Stone - LRV: 52.91 Polar Grey - LRV: 42.53</p> <p>Infills</p> <p>Smooth Textured PVC</p> <p>Black - LRV: 4.47 Light Grey - LRV: 12.74 Polar Grey - LRV: 42.73 Porth Stone - LRV: 53.11</p> <p>Infills</p> <p>Olympic Grip</p> <p>Black - LRV: 4.85</p>
Drilling	<p>Drilled for concealing plugs Undrilled Drilled with retro fit infill</p>
Screw Size	6
Application	For abutting to LVT and Vinyl to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Installation guide available.
Suitability	Light to medium foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, offices and apartment buildings.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Infill Options



Infill	Castellated PVC Insert
Material	PVC Compound
Slip Resistance Values	SRV Wet: 76 SRV Dry: 85
Drilling	Drilled for concealing plugs Undrilled Drilled with retro fit infill
Suitability	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.



Infill	Smooth Textured PVC Insert
Material	PVC Compound
Slip Resistance Values	SRV Wet: 56 SRV Dry: 65
Drilling	Drilled for concealing plugs Undrilled Drilled with retro fit infill
Suitability	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.



Infill	ATI49.5 Aluminium Insert
Material	Aluminium Alloy 6063 T6

Slip Resistance Values	SRV Wet: 54 SRV Dry: 82
Drilling	Undrilled Drilled with retro fit infill
Suitability	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings. Black Anodised AT149.5 inserts are suitable for stairs with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.

Infill	Olympic Grip Insert
Material	Aluminium Oxide
Finishes Available	Black
Slip Resistance Values	SRV Wet: 71 SRV Dry: 102
Drilling	Undrilled Drilled with retro fit infill
Suitability	Very heavy interior foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Made with Precision, Finished with Care

Carpet Accessory Trims Limited. Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com