



Product Technical Data Sheet



Catalogue Reference	AN81
Uniclass2015	Pr_35_90_31_74 RIGID STAIR NOSINGS
General Description	Single Channel/Bull Nose Stair Nosing. Supplied with choice of infill.
Nosing Construction	Stair Nosing With Infill
Material	Aluminium Alloy 6063 T6
Tread Dimension	68 mm
Nose Dimension	40 mm
Gauge	5.0 mm
Supplied Cut To Size, up to a maximum length of	3200 mm
Finishes Available & Light Reflective Values	<p>Satin Aluminium - LRV: 65.40</p> <p><b>Infills</b></p> <p><b>Castellated PVC</b></p> <p>Black - LRV: 4.25          Nimbus - LRV: 4.77          Regency - LRV: 5.16          Rustic - LRV: 5.52          Claret - LRV: 5.83          Peat - LRV: 5.88          Spruce - LRV: 6.38          Mid Blue - LRV: 6.53          Granite - LRV: 7.02          Jade - LRV: 7.33          Poppy - LRV: 10.01          Olive - LRV: 10.27          Fawn - LRV: 11.27          Flint - LRV: 11.27          Light Grey - LRV: 12.33          Gold - LRV: 16.84          Ivory - LRV: 37.42          Polar Grey - LRV: 42.53          Porth Stone - LRV: 52.91          Yellow - LRV: 54.91          Cloud - LRV: 55.18          White - LRV: 84.22</p>

	<p><b>Infills</b></p> <p><b>Smooth Textured PVC</b></p> <p>Black - LRV: 4.47  Light Grey - LRV: 12.74  Polar Grey - LRV: 42.73  Porth Stone - LRV: 53.11</p> <p><b>Infills</b></p> <p><b>ATI49.5 Aluminium</b></p> <p>Black Anodised - LRV: 4.80  Bronze - LRV: 10.10  Light Bronze - LRV: 27.25  Satin Aluminium - LRV: 65.40  Mill Aluminium - LRV: 71.65  Polished Aluminium - LRV: 75.55</p> <p><b>Infills</b></p> <p><b>Olympic Grip</b></p> <p>Black - LRV: 4.85</p>
<b>Screw Size</b>	8
<b>Compatible Products</b>	ANEXT, ANRE25, ANE NAP
<b>Additional Information</b>	This product is also available in Mill Aluminium with a heavy-duty anti-slip glass-fibre reinforced plastic infill for external/wet installations. Product Reference: AN81 GRP
<b>Application</b>	For abutting to carpet and carpet tiles to finish the nose edge of stairs. Can be rebated to sit flush in wooden steps. Compatible with profiles ANE Nap Detail, ANRE25 Ramp Detail and ANEXT extension tread. Installation guide available.
<b>Suitability</b>	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.
<b>Post Consumer Recyclability</b>	This product is 100% recyclable at suitable disposal centres.

# Infill Options



<b>Infill</b>	Castellated PVC Insert
<b>Material</b>	PVC Compound
<b>Slip Resistance Values</b>	SRV Wet: 76 SRV Dry: 85
<b>Drilling</b>	Drilled for concealing plugs Undrilled Drilled with retro fit infill



<b>Infill</b>	Smooth Textured PVC Insert
<b>Material</b>	PVC Compound
<b>Slip Resistance Values</b>	SRV Wet: 56 SRV Dry: 65
<b>Drilling</b>	Drilled for concealing plugs Undrilled Drilled with retro fit infill



<b>Infill</b>	ATI49.5 Aluminium Insert
<b>Material</b>	Aluminium Alloy 6063 T6
<b>Slip Resistance Values</b>	SRV Wet: 54 SRV Dry: 82

<b>Drilling</b>	Undrilled Drilled with retro fit infill
-----------------	--



<b>Infill</b>	Olympic Grip Insert
<b>Material</b>	Aluminium Oxide
<b>Slip Resistance Values</b>	SRV Wet: 71 SRV Dry: 102
<b>Drilling</b>	Undrilled Drilled with retro fit infill

**Made with Precision, Finished with Care**

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

[sales@catflooringaccessories.com](mailto:sales@catflooringaccessories.com)

[www.catflooringaccessories.com](http://www.catflooringaccessories.com)