



Product Technical Data Sheet



Catalogue Reference	ANEXT GRP
Uniclass2015	Pr_35_90_31_74 RIGID STAIR NOSINGS
General Description	Single Channel Stair Tread Extender. Supplied with GRP infill.
Nosing Construction	Stair Nosing With Infill
Material	Aluminium Alloy 6063 T6
Tread Dimension	63.5 mm
Gauge	5.0 mm
Supplied Cut To Size, up to a maximum length of	2400 mm
Finishes Available & Light Reflective Values	<p>Mill Aluminium - LRV: 71.65</p> <p>Infills</p> <p>GRPTI49.5 Infill</p> <p>Black - LRV: 4.76</p> <p>Yellow - LRV: 32.13</p> <p>Grey - LRV: 47.07</p>
Screw Size	8
Compatible Products	AN51 GRP, AN61 GRP, AN51/55 GRP, AN51/55R GRP, AN69 GRP, AN81 GRP, AN52 GRP, AN52R GRP, AN82 GRP, ANRE25
Application	To extend the going cover of heavy duty aluminium stair nosings with GRP inserts which have an interlock feature at the back edge. Can be used in combination with ANRE25 Ramp Detail to finish the nose edge of stone and timber stairs and stairs fitted with ceramics and hard flooring. Installation guide available.
Suitability	Exterior and wet environments and very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Infill Options



Infill	GRPTI49.5 Infill
Material	Glass-reinforced plastic with quartz grit bonded on top (with resin)
Slip Resistance Values	SRV Wet: 73 SRV Dry: 81
Drilling	Drilled with retro fit infill Undrilled with infill stuck in channel Undrilled with infill supplied loose

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com