

Product Technical Data Sheet



Catalogue Reference	ATI49.5
Uniclass2015	Pr_35_90_31_84 STAIR TRIMS
General Description	Aluminium Stair Tread Insert
Material	Aluminium Alloy 6063 T6
Tread Dimension	49.5 mm
Gauge	2.7 mm
Lengths Available	2750 mm
Finishes Available & Light Reflective Values	Satin Aluminium - LRV: 65.4
Slip Resistance Values	SRV Wet: 54 SRV Dry: 82
Fixing	Adhesive. We recommend Stycco Flex rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.
Drilling	Undrilled
Application	For rebating into stone and wooden steps or between ceramic tiles, to provide a visual aid and some slip resistance. Can also be supplied as a tread insert with CAT aluminium stair nosing profiles with equivalent infill pocket dimensions for an all- aluminium installation where concealed fixings are required. Installation guide available.
Suitability	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

**Made with Precision, Finished with Care**

Carpet Accessory Trims Limited. Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com