


Product Technical Data Sheet



Catalogue Reference	BID50
Uniclass2015	Pr_35_90_31_84 STAIR TRIMS
General Description	Stair Tread Insert Disc
Material	Solid Brass Grade H/H CZ108 BS EN 12164:2016
Gauge	4.8 mm
Pack Quantity	25
Diameter	50 mm
Finishes Available & Light Reflective Values	Antique Brass - LRV: 29.55
Slip Resistance Values	SRV Wet: 45 SRV Dry: 73
Fixing	Adhesive. We recommend STYCCO FLEX rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.
Application	For rebating into stone and wooden steps to provide a visual aid and slip resistance. Small variations in dimensions may occur and therefore rebating should be to suit the delivered product. Installation guide available.
Suitability	Medium to heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings. Please Note: Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are designed to create an aged, unpolished effect.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com