CAT | FLOORING ACCESSORIES

Updated: May 2026

Product Technical Data Sheet



Catalogue Reference	BN55
Uniclass2015	Pr_35_90_31_74 RIGID STAIR NOSINGS
General Description	Single Channel/Square Front Stair Nosing. Supplied with choice of infill.
Nosing Construction	Stair Nosing With Infill
Material	Solid Brass Grade H/H CZ108 BS EN12164:2016
Tread Dimension	59.5 mm
Nose Dimension	55 mm
Gauge	5.0 mm
Supplied Cut To Size, up to a maximum length of	2700 mm
Finishes Available & Light Reflective Values	Antique Brass - LRV: 29.55 **Infills** **BTI49.5 Brass** Antique Bronze - LRV: 9.15 Antique Brass - LRV: 29.55 Satin Brass - LRV: 59.55 Polished Brass - LRV: 71.45 **Infills** **Smooth Textured PVC** Black - LRV: 4.47 Light Grey - LRV: 12.74 Polar Grey - LRV: 42.73 Porth Stone - LRV: 53.11 **Infills** **Castellated PVC** Black - LRV: 4.25 Nimbus - LRV: 4.77 Regency - LRV: 5.16 Rustic - LRV: 5.52 Claret - LRV: 5.83 Peat - LRV: 5.88 Spruce - LRV: 6.38 Mid Blue - LRV: 6.53

	Granite - LRV: 7.02 Jade - LRV: 7.33 Poppy - LRV: 10.01 Olive - LRV: 10.27 Fawn - LRV: 11.27 Flint - LRV: 11.27 Light Grey - LRV: 12.33 Gold - LRV: 16.84 Ivory - LRV: 37.42 Polar Grey - LRV: 42.53 Porth Stone - LRV: 52.91 Yellow - LRV: 54.91 Cloud - LRV: 55.18 White - LRV: 84.22 Infills Olympic Grip Black - LRV: 4.85
Screw Size	8
Compatible Products	BNE NAP, BNFE 30
Application	To butt up to flooring, or installed with BNE brass naplock profile for carpet installations and BNFE30 ramp profile for retrofit installations.
Suitability	Medium to heavy foot traffic in interior situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings. Please Note: Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are designed to create an aged, unpolished effect.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Infill Options

Infill	BTI49.5 Brass Insert
Material	Solid Brass Grade H/H CZ108 BS EN12164:2016
Slip Resistance Values	SRV Wet: 54 SRV Dry: 82
Drilling	Undrilled Drilled with retro fit infill

Infill	Smooth Textured PVC Insert
Material	PVC Compound
Slip Resistance Values	SRV Wet: 56 SRV Dry: 65
Drilling	Drilled for concealing plugs Undrilled Drilled with retro fit infill



Infill	Castellated PVC Insert
Material	PVC Compound
Slip Resistance Values	SRV Wet: 76 SRV Dry: 85

Drilling	Drilled for concealing plugs Undrilled Drilled with retro fit infill

Infill	Olympic Grip Insert
Material	Aluminium Oxide
Slip Resistance Values	SRV Wet: 71 SRV Dry: 102
Drilling	Undrilled Drilled with retro fit infill

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500 sales@catflooringaccessories.com www.catflooringaccessories.com