CAT | FLOORING ACCESSORIES

Updated: May 2026

Product Technical Data Sheet



Catalogue Reference	BTI52
Uniclass2015	Pr_35_90_31_84 STAIR TRIMS
General Description	Stair Tread Insert
Material	Solid Brass Grade H/H CZ108 BS EN 12164:2016
Tread Dimension	52 mm
Gauge	4.8 mm
Visible Surface When Installed	52 mm
Supplied Cut To Size, up to a maximum length of	3200 mm
Finishes Available & Light Reflective Values	Polished Brass - LRV: 71.45
Slip Resistance Values	SRV Wet: 45 SRV Dry: 73
Fixing	Adhesive. We recommend Stycco Flex rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.
Drilling	Undrilled
Compatible Products	BN67, BN67R, BN1, BN4, BN90, BN2, BN11
Alternative Use	Stair Nosing Tread Extender
Application	For rebating into stone and wooden steps or between ceramic tiles, to provide a visual aid and some slip resistance. Can be used in combination with stair nosings of equivalent thickness to create extended step going cover. Installation guide available.
Suitability	Heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK