


Product Technical Data Sheet



|  |   |
|--|---|
| Catalogue Reference                          | FPA 4.5x3   |
| Uniclass2015                                 | Pr_35_90_31_84 STAIR TRIMS  |
| General Description                          | Stair Tread Insert Flat Plate   |
| Material                                     | Aluminium Alloy 6063 T6   |
| Height                                       | 4.5 mm  |
| Lengths Available                            | 2715 mm   |
| Finishes Available & Light Reflective Values | Light Bronze - LRV: 27.25   |
| Fixing                                       | Adhesive. We recommend STYCCO FLEX rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.   |
| Alternative Use                              | Floor and Wall Inlay Strip  |
| Application                                  | For rebating into stone and wooden steps to provide a visual aid and some slip resistance or for creating flooring features. Small variations in dimensions may occur and therefore rebating should be to suit the delivered product. Installation guide available. |
| Suitability                                  | For installations with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.  |
| Post Consumer Recyclability                  | This product is 100% recyclable at suitable disposal centres.   |

**Made with Precision, Finished with Care**

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com