CAT | FLOORING ACCESSORIES

Updated: May 2026

Product Technical Data Sheet



Catalogue Reference	FPA 16x3
Uniclass2015	Pr_35_90_31_84 STAIR TRIMS
General Description	Stair Tread Insert Flat Plate
Material	Aluminium Alloy 6063 T6
Height	16 mm
Lengths Available	2715 mm
Finishes Available & Light Reflective Values	Bronze - LRV: 10.10
Fixing	Adhesive. We recommend STYCCO FLEX rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.
Alternative Use	Floor and Wall Inlay Strip
Application	For rebating into stone and wooden steps to provide a visual aid and some slip resistance or for creating flooring features. Small variations in dimensions may occur and therefore rebating should be to suit the delivered product. Installation guide available.
Suitability	For installations with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500 sales@catflooringaccessories.com www.catflooringaccessories.com