

Product Technical Data Sheet



| | |
|--|--|
| Catalogue Reference | FPA 16x3 |
| Uniclass2015 | Pr_35_90_31_30 FLOOR DIVIDING STRIPS |
| General Description | Floor and Wall Inlay Strip |
| Material | Aluminium Alloy 6063 T6 |
| Height | 16 mm |
| Visible Surface When Installed | 3 mm |
| Lengths Available | 2715 mm |
| Finishes Available & Light Reflective Values | Light Bronze - LRV: 27.25 |
| Fixing | Adhesive. We recommend STYCCO FLEX rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use. |
| Alternative Use | Stair Tread Insert Flat Plate |
| Application | For inserting between floor finishes to create design features. Installation guide available. |
| Suitability | For installations with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath. |
| Post Consumer Recyclability | This product is 100% recyclable at suitable disposal centres. |

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com