CAT FLOORING ACCESSORIES

Updated: May 2026

Product Technical Data Sheet



Catalogue Reference	FPN60-83
Uniclass2015	Pr_35_90_31_84 STAIR TRIMS
General Description	Castellated Tread/Raked Front Stair Nosing.
Material	PVC Compound
Tread Dimension	60 mm
Nose Dimension	30 mm
Gauge	2.5 mm
Lengths Available	2750 mm
Colours & Light Reflective Values	Yellow (TSO) - LRV: 55.11
Slip Resistance Values	SRV Wet: 76 SRV Dry: 85
Fixing	Supplied undrilled for adhesive fixing. *We recommend STYCCO FLEX rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.
Drilling	Undrilled
Application	To provide a neat and protective edge to LVT, vinyl and lino flooring on stairs and plinths where a traditional stair nosing is not required.
Suitability	Light foot traffic in commercial and residential applications.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500 sales@catflooringaccessories.com www.catflooringaccessories.com