



Product Technical Data Sheet



Catalogue Reference	GRPTI62
Uniclass2015	Pr_35_90_31_84 STAIR TRIMS
General Description	Stair Tread Insert
Nosing Construction	Stair Nosing With Infill
Material	Aluminium Alloy 6063 T6
Tread Dimension	62 mm
Nose Dimension	5 mm
Gauge	5.0 mm
Supplied Cut To Size, up to a maximum length of	2400 mm
Finishes Available & Light Reflective Values	Mill Aluminium - LRV: 71.65 <b>Infills</b> <b>GRPTI49.5 Infill</b> Black - LRV: 4.76 Yellow - LRV: 32.13 Grey - LRV: 47.07
Screw Size	8
Application	For rebating into stone and wooden steps or with ceramic tiles, to provide a visual aid and some slip resistance. Installation guide available.
Suitability	Exterior and wet environments and very heavy foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

# Infill Options



<b>Infill</b>	GRPTI49.5 Infill
<b>Material</b>	Glass-reinforced plastic with quartz grit bonded on top (with resin)
<b>Slip Resistance Values</b>	SRV Wet: 73 SRV Dry: 81
<b>Drilling</b>	Drilled with retro fit infill Undrilled with infill stuck in channel Undrilled with infill supplied loose

## Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

[sales@catflooringaccessories.com](mailto:sales@catflooringaccessories.com)

[www.catflooringaccessories.com](http://www.catflooringaccessories.com)