CAT | FLOORING ACCESSORIES

Updated: May 2026

Product Technical Data Sheet



Catalogue Reference	KKSBP9.5
Uniclass2015	Pr_35_90_31_90 TWO PART FLOOR TRANSITION STRIPS
General Description	Kliks Slim Base
Brand	Kliks Slim®
Material	uPVC
Recycled Factory Stream Waste (%)	85%
External Height	9.5 mm
Lengths Available	900 mm 2715 mm
Colours & Light Reflective Values	Black uPVC - LRV: 4.25
Standard Supply	Supplied with an unpunched base for adhesive fixing or for bedding into ceramic mortar.
Compatible Products	KKSLRDHC (Aluminium), Kliks Slim Ramp Top (Brass), KKSLTTDHC (Aluminium), Kliks Slim Twin Top (Brass), Kliks Slim Twin Top (Stainless Steel), Kliks Slim End Stop (Aluminium), Kliks Slim Long End Stop (Aluminium), Kliks Slim End Stop with Expansion/Compression Feature (Aluminium), Kliks Slim End Stop without Expansion/Compression Feature (Aluminium), Kliks Slim End Stop (Brass)
Application	Installed by adhesive/mortar fixing to the substrate floor. Flooring material fitted before chosen top profile clipped into place.
Suitability	Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500 sales@catflooringaccessories.com www.catflooringaccessories.com