


Product Technical Data Sheet



Catalogue Reference	KKSL20 Kliks Slim Twin Top
Uniclass2015	Pr_35_90_31_90 TWO PART FLOOR TRANSITION STRIPS
General Description	Kliks Slim Twin Top
Brand	Kliks Slim™
Material	Solid Brass Grade H/H CZ108 BS EN 12164:2020
Height adjustment	8 mm to 20 mm, depending on chosen base
Expansion on Sides	Allows up to 10mm expansion on each side.
Visible Surface When Installed	30 mm
Lengths Available	2715 mm 900 mm
Finishes Available & Light Reflective Values	Antique Brass - LRV: 29.55
Standard Supply	Undrilled.
Compatible Products	KKSBP9.5, KKSBP12, KKSBP15, KKSBP20
Application	Installed in combination with one of five compatible bases to protect the edges of the floor coverings. The chosen KSBP base is firmly affixed to the substrate floor then the top pressed down over it to engage interlock feature between the two profiles. Ideal for finishing timber, ceramic tiles, laminates and any other flooring that requires expansion.
Suitability	Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public building, as well as for quality domestic installations. Please Note: Antique Brass and Antique Bronze finishes are a chemically applied process and are hand finished with a variance from batch to batch. They are designed to create an aged, unpolished effect.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

Made with Precision, Finished with Care

Carpet Accessory Trims Limited. Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com