


Product Technical Data Sheet



Catalogue Reference	Olympic ATI49.5
Uniclass2015	Pr_35_90_31_84 STAIR TRIMS
General Description	Olympic Grip Stair Tread Insert on Aluminium Carrier
Material	Base: Aluminium Alloy 6063 T6, Surface: Aluminium Oxide on PVC Carrier
Tread Dimension	50 mm
Gauge	4.0 mm
Supplied Cut To Size, up to a maximum length of	2500 mm
Finishes Available & Light Reflective Values	Black Olympic Grip Infills Olympic Grip Black - LRV: 4.85
Fixing	Adhesive. We recommend STYCCO FLEX rapid curing flexible adhesive by F. Ball & Co Ltd. subject to following their instructions for use.
Drilling	Undrilled
Application	For rebating into stone and wooden steps or between ceramic tiles, to provide a visual aid and some slip resistance. Suitable of exterior and interior applications. Installation guide available.
Suitability	Very heavy interior foot traffic situations such as in hotels, pubs, clubs, cafes, shops, schools, commercial offices and apartment buildings.

Infill Options



Infill	Olympic Grip Insert
Material	Aluminium Oxide
Slip Resistance Values	SRV Wet: 71 SRV Dry: 102

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com