


Product Technical Data Sheet



Catalogue Reference	RBD16
Uniclass2015	Pr_35_90_31_58 ONE PART FLOOR TRANSITION STRIPS
General Description	Movement Joint
Brand	Reflex®
Material	Angle Profile: Matt finish brass alloy to BS2874:1986. Expansion Media: Polyurethane Elastomer with a hardness of 48+/- Shore A which, under pressure will compress readily by 20%. Highly chemical and stain resistant.
Expansion Medium Material	Polyurethane Elastomer with a hardness of 48+/- Shore A which, under pressure will compress readily by 20%. Highly chemical and stain resistant.
Internal Height	14.5 mm
External Height	16 mm
Visible Surface When Installed	15 mm
Lengths Available	2715 mm
Finishes Available & Light Reflective Values	Matt Brass - LRV: 60.55
Standard Supply	Punched base for adhesive fixing.
Suitability	Can be fitted over underfloor heating systems operating within normal temperature ranges of such installations, up to a maximum of 30°C. For environments where profiles will be exposed to high levels of chemicals or immersion, please discuss your requirements with our technical sales office.
Post Consumer Recyclability	The expansion media is not currently recycled so, at the end of product life, the polyurethane elastomer should be separated from the metal carrier and disposed of by licensed waste disposal in landfill. The metal angles are recyclable and may also have monetary value which will encourage the recycling process.

Made with Precision, Finished with Care

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com