


Product Technical Data Sheet



Catalogue Reference	Timberline 1/22A
Uniclass2015	Pr_35_90_31_58 ONE PART FLOOR TRANSITION STRIPS
General Description	Profile for Timber Floors
Brand	Timberline®
Material	Aluminium Alloy 6063 T8
Gauge	1.5 mm
Internal Height	22 mm
Visible Surface When Installed	15 mm
Lengths Available	2500 mm
Finishes Available & Light Reflective Values	Satin Aluminium - LRV: 65.40 Please note, finishes are to the top visible edge only.
Standard Supply	Drilled through the base for mechanical fixing using size 6 screws or supplied undrilled with Stick Fix double-sided adhesive tape pre-applied to the outside of the vertical surface for non-mechanical fixing.
Drilling	Undrilled with Stick Fix double sided adhesive tape pre-applied Drilled
Alternative Use	Perimeter Trim
Suitability	Medium to heavy contract situations such as for use in hotels, pubs, cafes, clubs, commercial offices, shops, schools and public buildings, as well as for quality domestic installations.
Additional Information	Bespoke Sizes are available to Special Order.
Post Consumer Recyclability	This product is 100% recyclable at suitable disposal centres.

**Made with Precision, Finished with Care**

CAT Flooring Accessories, Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com