

Maintenance Guide

Product Range:	ALUMINIUM FLOORING PROFILES
Materials:	Aluminium Alloy 6063 T6
General:	<p>Immediately after installation and the removal of protective tape, the flooring profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.</p> <p>These aluminium profiles are produced with a highly polished, satin, or mill finish.</p> <p>The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance and adversely affect performance.</p>
Polished Finish:	<p>Polished aluminium profiles require polishing with a suitable metal polish and a soft cloth in order to maintain their appearance. Make sure that all traces of polish are removed during polishing.</p> <p>Do not allow polish build up on the profile section as this may cause slipping underfoot</p>
Satin Finish:	<p>Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth.</p> <p>To remove scuffs and small scratches, a green or red Scotch pad can be used, rubbing along the grain of the existing finish.</p>
Mill Finish:	<p>Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth.</p> <p>To remove light scuff marks, use a fine grade wire wool.</p>
Important:	<p>Ensure that all surfaces are wiped dry after cleaning before allowing pedestrian access.</p> <p>Care must be taken to protect surrounding floor finishes during maintenance.</p>

Made with Precision, Finished with Care

CAT LTD. Units 24 A,B,C, Park Avenue Estate, Luton, Bedfordshire LU3 3BP, U.K.

T: +44 (0) 1582 561 500

email: sales@catflooringaccessories.com

website: www.catflooringaccessories.com