

Maintenance Guide

Product Range:	BLACK ANODISED FLOORING PROFILES
Material:	Aluminium Alloy 6063 T6
General:	<p>The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance. Immediately after installation and the removal of protective tape, the flooring profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.</p> <p>Black Anodising hardens the surface making it more scratch resistant than a painted finish. However, heavy foot traffic and careless goods handling can wear through the surface to reveal the natural aluminium colour beneath.</p>
Cleaning:	<p>Black Anodised finish can be cleaned using soap, warm water and a soft cloth. Do not use abrasive pads as these may scratch the surface.</p> <p>Sponge the soiled area with the solution, then rinse with clean water and dry.</p> <p>Prolonged exposure to damp environments, acids or strong alkali solutions may lead to corrosion of the metal.</p>
Important:	<p>Ensure that all surfaces are wiped dry after cleaning before allowing pedestrian access.</p> <p>Care must be taken to protect surrounding floor finishes during maintenance.</p>

Made with Precision, Finished with Care

CAT LTD. Units 24 A,B,C, Park Avenue Estate, Luton, Bedfordshire LU3 3BP, U.K.

T: +44 (0) 1582 561 500

email: sales@catflooringaccessories.com

website: www.catflooringaccessories.com