

Maintenance Guide

Product Range:	AC38 DHC (Designer Home Collection)
Materials:	Aluminium Alloy 6063 T6
General:	<p>The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance. Immediately after installation and the removal of protective tape, the flooring profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.</p> <p>AC38 DHC is available in all DHC finishes.</p> <p>DHC finishes are an applied process and are not heavy foot-traffic resistant.</p>
Cleaning:	<p>DHC finishes can be cleaned using soap and warm water.</p> <p>Sponge the soiled area with the solution, then rinse with clean water and dry.</p> <p>Prolonged exposure to damp environments, acids or strong alkali solutions may lead to corrosion of the metal.</p>
Important:	<p>Ensure that all surfaces are wiped dry after cleaning before allowing pedestrian access.</p> <p>Care must be taken to protect surrounding floor finishes during maintenance.</p>

Made with Precision, Finished with Care

CAT LTD. Units 24 A,B,C, Park Avenue Estate, Luton, Bedfordshire LU3 3BP, U.K.

T: +44 (0) 1582 561 500

email: sales@catflooringaccessories.com

website: www.catflooringaccessories.com