

## Maintenance Guide

**Product Range:****Powder coated aluminium flooring profiles****Material:**

Aluminium Alloy 6063 T6

**General:**

Immediately after installation and the removal of protective tape, the flooring profile should be wiped with a dry, soft cloth to remove any handling marks and fingerprints.

Our powder coated aluminium floor trims are produced to Qualicoat standard specification. For RAL colour availability and suitability on individual floor trims always contact our Sales Team.

The installed profile should be swept clean on a daily basis to avoid build up of dust and dirt which may make it more difficult to maintain its appearance and adversely affect performance.

Our powder coated floor trims are suitable for installations in areas with low to medium traffic volumes. Heavy foot traffic and impact damage can wear through the finish to reveal the natural aluminium colour beneath.

**Cleaning****Powder Coat Finish:**

Wipe clean with a mild detergent, diluted with water, on a damp, not wet, cloth. Do not use abrasive pads as these may scratch the surface.

Sponge the soiled area with the solution, then rinse with clean water and dry.

Prolonged exposure to damp environments, acids or strong alkali solutions may lead to corrosion of the metal.

**Important:**

**Ensure that all surfaces are wiped dry after cleaning before allowing pedestrian access.  
Care must be taken to protect surrounding floor finishes during maintenance.**

**Made with Precision, Finished with Care**

CAT Flooring Accessories, Units 24 A,B,C, Park Avenue Estate, Luton, Bedfordshire LU3 3BP, U.K.

T: +44 (0) 1582 561 500

email: [sales@catflooringaccessories.com](mailto:sales@catflooringaccessories.com)

website: [www.catflooringaccessories.com](http://www.catflooringaccessories.com)