

Product Technical Data Sheet



Catalogue Reference	HPBT 3904 - Stick Fix®
Uniclass2015	Pr_40_90_08_05 Adhesive tapes
General Description	Tape for flooring trims and accessories for non-mechanical installations. Pressure sensitive adhesive exhibiting high levels of adhesion and cohesion.
Colour	Pale amber
Standard Supply	Supplied pre-applied to flooring trims and accessories.
Service Temperature Range	-10°C to +60°C
Application Temperature	+10°C
Softening Point	Approx. 75°C (Ring&Ball) XLA QA502
Shear	>1595.0 (FTM 8 @ 40°C 10N/in ²)
Peel Adhesion 180° N/25mm	25.5 (FTMI)
Appearance	Solid Straw/Translucent coloured Tape on Liner
Suitability	FDA Status: Approved under FDA 21 CFR 175.104 for direct food contact. Designed to provide a durable bond throughout the expected service life of the flooring trim, stair nosing accessory or wall protection profile, subject to correct installation, substrate condition and service environment.
Storage	Until installed, store in a clean and dry environment in a closed container between 5°C and 35°C.
Expected Service Life	Under normal internal conditions and when installed in accordance with CAT recommendations, Stick Fix® is designed to provide long-term service performance throughout the expected life of the associated CAT flooring trim, stair nosing accessory or wall protection profile.
Important Information	Not recommended where prolonged UV resistance, aggressive chemical resistance or continuous water immersion is required.
Post Consumer Recyclability	The profile this tape is pre-applied to may be 100% recyclable at suitable disposal centres. For more information, please check the Technical Datasheet of the profile the tape is pre-applied to.

Made with Precision, Finished with Care

Carpet Accessory Trims Limited. Units 24 A,B,C Park Avenue Estate, Luton, Bedfordshire LU3 3BP, UK

+44 (0) 1582 561 500

sales@catflooringaccessories.com

www.catflooringaccessories.com